



Laminated Wood Products

Minimum purchase quantity for pick-up: supplied on a commission basis • Minimum purchase quantity for delivery: 1 truck

SCHAFFERHOLZ

| | Window Scantlings | | | |
|--|-------------------|---|-----------|---|
| | Types of wood | spruce, Austrian larch, Siberian larch, fir, oak | Thickness | 42, 48, 63, 72 mm |
| | Quality | lamellae in rift and half-rift multi-bonded with D4 glue according to EN 204 (formaldehyde-free), with continuously flawless covering plies, wedge-finger jointed middle plies Production monitored by Holzforschung Austria | Width | 86, 88, 91, 95, 115 mm |
| | | | Length | 500 to 3000 mm, other dimensions on request |
| | | | Usage | windows and doors, sliding doors, creative interior finishing work, in external areas not constantly under strain from atmospheric conditions |

| | House Door Mouldings | | | |
|--|----------------------|---|-----------|---|
| | Types of wood | spruce, Austrian larch, Siberian larch, fir, oak | Thickness | 42, 48, 63, 72, 75 mm |
| | Quality | lamellae in rift and half-rift multi-bonded with D4 glue according to EN 204 (formaldehyde-free), with continuously flawless covering plies, wedge-finger jointed middle plies Production monitored by Holzforschung Austria | Width | 86, 88, 91, 95, 115 mm |
| | | | Length | 500 to 3000 mm, other dimensions on request |
| | | | Usage | windows and doors, sliding doors, creative interior finishing work, in external areas not constantly under strain from atmospheric conditions |

| | Finger Jointed Scantlings | | | |
|--|---------------------------|--|-----------|---|
| | Types of wood | spruce, Austrian larch, Siberian larch, fir, oak | Thickness | 42, 48, 63, 72, 75 mm |
| | Quality | multi-bonded with D4 glue according to EN 204 (formaldehyde-free); wedge-finger jointed covering plies with 25 cm minimum length/piece of wedge-finger jointing, all ply lengths are wedge-finger jointed Production monitored by Holzforschung Austria | Width | 86, 88, 91, 95, 115 mm, other dimensions on request |
| | | | Length | to 6050 mm |
| | | | Usage | windows and doors, sliding doors, creative interior finishing work, in external areas not constantly under strain from atmospheric conditions |

| | Flawless Finger Jointed Construction Wood | | | |
|--|---|---|-----------|--|
| | Types of wood | spruce, larch, fir | Thickness | 72, 120, 168, 216, 264, 312 mm |
| | Quality | multi-bonded, flawless (without knots), wedge-finger jointed, bonded with D4 glue according to EN-204 (formaldehyde-free) | Width | 86, 91, 105, 115, 120 mm |
| | | | Length | 3000 to 6000 mm |
| | | | Usage | for creating winter gardens and interior works |

| | Finger Jointed Construction Battens | | | |
|--|-------------------------------------|-------------------------------------|-----------|---------------------|
| | Types of wood | spruce, larch, fir | Thickness | on customer request |
| | Quality | on customer request | Width | on customer request |
| | Design | topped raw battens, rough or planed | Length | on customer request |
| | | | | |

| | Construction Boards | | | |
|--|---------------------|---|--------|---|
| | Types of wood | spruce, larch | Width | 340, 600, 1210 mm |
| | Quality | flawless (without knots and resin galls), wedge-finger jointed, bonded with D4 glue according to EN-204 (formaldehyde-free) | Length | 3000 to 5000 mm |
| | | | Usage | in creative furniture and interior works as well as in external areas not constantly under strain from atmospheric conditions (stairwells, steps, window sills, worktops, table tops, furniture fronts) |
| | Thickness | 20, 30, 40, 50, 60 mm | | |

| | Single-Layer Solid Wood Boards | | | |
|--|--------------------------------|---|-----------|---|
| | Types of wood | spruce, fir | Thickness | 18, 23, 28 mm |
| | Quality | flawless (without knots and resin galls), stab-jointed rift products with continuous or wedge-finger jointed lamellas in various qualities, bonded with D4 glue according to EN-204 (formaldehyde-free) | Width | 600, 1010, 1210 mm |
| | | | Length | 3000 to 5000 mm |
| | | | Usage | furniture construction (fronts, wood casings) |

| | Flawless Solid Wood Battens | | | |
|--|-----------------------------|---|--------|---|
| | Types of wood | spruce, larch, fir | Width | on customer request |
| | Quality | planed or un-planed, wedge-finger jointed or continuous | Length | from 200 mm, wedge-finger jointed up to 6 m possible |
| | | | Usage | for concealed edge bands for doors, window bar frames, transom frames, beam moulding frames or picture frames |
| | Thickness | on customer request | | |

| | Schaffer Holz Brikks | | |
|--|---|--|--|
| | Are the environmentally-friendly alternative to heat in a modern way. Schaffer-HolzBrikks can be used instead of split logs. When they burn, they are incredibly low in pollutants and emissions and are made from clean sawdust without using binding agents or additives Inspected in accordance with ÖNORM M 7135 (Reg.No. ON-N 2007079) and DIN 51731 (Reg. No. 5HO95). | | |
| | Minimum purchase quantity for pick-up: 1 palette = 100 packets each containing 10kg = 1 ton | | |
| | Minimum purchase quantity for delivery: 24 ton = 1 truck | | |
| | | | |